

				SUMSONG
		Serie B450/B457/B550	19 HD	22 HD
Basic Info		Model Code	LE19B450C4H & LE19B451C4H (White)	LE22B450C4H & LE22B451C4H (White)
		Screen Size	19"	22"
		HD Ready/FHD	HD Ready	HD Ready
		Resolution	1366 X 768	1366 X 768
	Video	Response Time	6ms	6ms
	Video	Viewing angle (H/V)	170/160	170/160
		Backlight	CCFL	CCFL
		Dynamic Contrast Ratio	15,000:1	15,000:1
		Brightness	300cd/m ²	300cd/m²
		Output	2 X 3W	2 X 3W
		Stereo	A2/NICAM	A2/NICAM
Audio		Surround May Internal Speaker Out	SRS Trusurround HD 3W L/R	SRS Trusurround HD 3W L/R
		Max Internal Speaker Out Bass Control Range	-8dB ~ +8dB	-8dB ~ +8dB
	Addio	Treble Control Range	-8dB ~ +8dB	-8dB ~ +8dB
		Headphone Out	10mW Max	10mW Max
		Output Frequency AV	80Hz-20kHz	80Hz-20kHz
		Bathroom Speaker Out	- -	
		Picture Engine		-
		Sleep Timer	Yes	Yes
		Auto TV On/Off timer	Yes	Yes
	Facture	Teletext	1000P Mega TTX	1000P Mega TTX
	Feature	Auto Channel Search	Yes	Yes
		Auto Volume Leveller	Yes	Yes
		Swivel (left/right)		
		OSD Language	25 Languages (Europe)	25 Languages (Europe)
	Output	Headphone	-	-
SIDE		S-Video	-	-
SIDE	Input	Composite AV	1	1
		HDMI		<u> </u>
		RF Input	1	1
	Input	Component(Y/Pb/Pr)	1	1
	Output	Headphone(Earphone)	1	1
	Input	Scart	1	1
		Composite(AV)	1	1
		HDMI	1	1
REAR		PC D-sub PC Audio Jack	1	<u> </u>
	Output	Audio Out (line Out) Monitor	<u>'</u>	<u> </u>
		Audio Out (Variable Out) BathroomSPK	-	-
		Optical sound out	1	1
	Input/Output	RJ12 For External Control	1	1
	Output	DC-out Jack	-	ı
		Hotel Mode	Yes	Yes
		Hotel Mode Plug & Play	Yes	Yes
		Music Mode (Input: PC/AV/Component)	Yes	Yes
		Music Mode Backlight on/off	Yes	Yes
		Audio Loop in (Headphone extension) 12V and 5V Power Supply for Set Top box		-
		Hotel TV (RJ12 / IR pass through)	Interactive	Interactive
		Clock (PMOLED Type)	-	-
		PMOLED Image Display	-	-
		PMOLED Clock Dimming Control	-	-
		PMOLED Clock Back Up Supply	-	-
Hospitality Feature		TTX Clock Update (Analogue)	-	-
		Auto Power Off After No Remote Function	After 3 Hours	After 3 Hours
		Power On Status Setting (Key Card / Master)	Yes	Yes
		Jack Pack Compatibility USB Cloning	Yes Yes	Yes Yes
		Bathroom Speaker output	Yes -	Yes -
		Multi Code Remote (Hospital)	Yes	Yes
		Secure Battery Cover	Yes	Yes
		Channel List	Standalone	Standalone
		Alarm Key	Standalone	Standalone
		Hotel logo display with time out setting	Yes	Yes
		Auto PC mode	Yes	Yes
		Energy Saving Mode	Low/Medium/High/Auto	Low/Medium/High/Auto



Serie B450/B457/B550		19 HD	22 HD
Basic Info		LE19B450C4H &	LE22B450C4H &
Dasic IIIIO	Model Code	LE19B451C4H (White)	LE22B451C4H (White)
	Weight (Set) With Stand (kg)	4,8	6,5
Dimension	Weight (Set) Without Stand (kg)	4,2	5,1
Dimension	Dimensions (WxDxH)mm With Stand	477.1*180.2*374	557.8*216*437.4
	Dimensions (WxDxH)mm Without Stand	477.1*65.5*326.9	557.8*75*384.1
	Remote Control	Yes	Yes
	Installation manual	Yes	Yes
Accessory	Batteries, AAA type	Yes	Yes
Accessory	ANT- Cable	No	No
	RJ 12 Cable	Yes	Yes
	Power Cable	Yes	Yes
VESA	Dimensions (mm)	75x75	75x75
VESA	Screw Size	M4	M4
System	Colour system	PAL/SECAM	PAL/SECAM
System	Tuner	DVB-C/T MPEG 2/4	DVB-C/T MPEG 2/4
	Power	AC220-240V 50Hz	AC220-240V 50Hz
Power	Power Consumption (Watts)	50W	60W
	Standby Power Consumption (Watts)	<1W	<1W
	Off	26W	45.8W
Energy Saving Mode	Low	21.8W	34.3W
Power Consumption	Medium	19W	30W
	High	17W	21.1W
Security	Kensington Lock	Yes	Yes
	Operating Temp	-10C ~ +60C	-10C ~ +60C
Environmental	Operating Humidity	30% ~ 95%	30% ~ 95%
Liivii Oiliileillai	Storage Temp	-30C ~ +60C	-30C ~ +60C
	Storage Humidity	0% ~ 90% Rh	0% ~ 90% Rh

Techn. Änderungen und Druckfehler vorbehalten